



1. STRANDED ALUMINIUM CONDUCTOR
2. XLPE INSULATION
3. NHLSFR INNER SHEATH
4. NHLSFR OUTER SHEATH

NEELKANTH CABLES LIMITED
DATA SHEET
FIVE CORE XLPE UNARMoured ZERO HALOGEN EMISSION, REDUCED SMOKE EMISSION AND REDUCED FLAME PROPAGATION (NHLSFR) LV POWER CABLE

Single Core Cable Description : Aluminium Conductor,XLPE Insulated,NHLSFR(Polyolefin) Inner Sheathed,Aluminium Wire Armoured, Overall NHLSFR(Polyolefin) Outer Sheathed Low Voltage Cable.

Make NEELKANTH CABLES LIMITED
 Reference Standard As per SANS:1507-5, ZS-688-5
 Voltage Grade 600/1000 Volt
 Operating Temperature 90°C
 Max. Temp. During Short Circuit 250°C

Range of Product 1.5 Sq.mm up to 500 Sq.mm

Application

These power and cables are used for electricity supply in low voltage installation system. they are well adapted to underground, outdoors, used in industrial applications where chemical and mechanical protections are needed .In particular for installation where fire,smoke emmission and toxic flumes create a potential threat.

Construction

Conductor Aluminium Conductor, round stranded or shaped class 2 to SANS 1411-1
 Insulation XLPE(Cross-linked Polyethylene)as per SANS 1411-4 & ZS 756 -4
 Insulation colour as per SANS 1507-5 & ZS 688-5
 4 Core : Red, Yellow,Blue, Black, Grey
 Filler (Optional) PVC or Polypropylene yarn
 Binder Tape (Optional) Polyester Tape
 Inner Sheath/Bedding NHLSFR(Zero Halogen Emission Reduced Smoke Emission and Reduced Flame Propagation,Polyolefin) as per SANS 1411-5
 Outer Sheath NHLSFR(Zero Halogen Emission Reduced Smoke Emission and Reduced Flame Propagation,Polyolefin) as per SANS 1411-5
 colour: Black with White Stripe or as per Requirement

Technical Characteristic

Voltage Grade 600/1000V
 Test Voltage Up to 16 Sq.mm 3 kV for 5 Minute, 25 Sq.mm and above 4.5 kV for 5 Minute
 Spark Test Voltage Up to and including 16 Sq.mm 6 kV
 Up to and including 240 Sq.mm 10 kV
 Above 240 Sq.mm 12 kV
 Insulation Volume Resistivity Minimum 1×10^{14} Ohm-cm
 Temperature Rating -15°C to +90°C
 Flame Retardent SANS 60332 Part -3
 Reduced Smoke Emission SANS 61034-2
 Halogen Gas SANS 60754-2
 Minimum Installation Bending Radius 8 x Overall Diameter

Marking & Packing

Marking over the sheath NEELKANTH CABLES , CABLE SIZE, 600/1000V, AL/XLPE/NHLSFR ELECTRIC CABLE , YEAR OF MANUFACTURING
 Sequentail Length Marking Shall be provided on outer sheath at every one Meter
 Cable Length Multiple of 250/500/1000 or as per Requirement
 Type of Drum Wooden Drum Fully Packed with Lagging

Data Sheet No.	10275	Page 1 of 1
Version	01	Issue Date: 29/04/2021